

Chemical Hose



Construction:

- Tube is clear ultra-high molecular weight polyethylene (UHMWPE)
- Cover is blue or green abrasion, weather, and ozone resistant EPDM rubber
- Reinforcement is multiple layers of high tensile nylon cord with dual helix wire

Operating Temperature:

- -40° F / +250° F (-40° C / +121° C)

Safety Factor:

- 4:1

Application:

- Pressure and suction application
- Can handle 98% of all types of chemicals, solvents, and corrosive liquids

Part Number	Hose I.D.		Hose O.D.		Working Pressure (psi)	Length (ft)	Min. Bend Radius (in)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)				
CHE-UHMW-0075-200	3/4	19	1.22	31	200	200	2	0.44
CHE-UHMW-0100-200	1	25	1.46	37	200	200	3	0.60
CHE-UHMW-0125-200	1-1/4	32	1.83	46	200	200	3.5	0.90
CHE-UHMW-0150-200	1-1/2	38	2.06	52	200	200	4	1.03
CHE-UHMW-0200-200	2	51	2.58	66	200	200	6	1.37
CHE-UHMW-0250-200	2-1/2	63	3.08	78	200	200	7.5	1.72
CHE-UHMW-0300-200	3	76	3.64	92	200	200	9	2.25
CHE-UHMW-0400-200	4	102	4.71	120	200	200	12	3.17

Coupled Assemblies In Stock!

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.