

Ceramic Hose



Tube: EPDM rubber with ceramic chip lining inside

Reinforcement: Polyester fabric and helix steel wire

Cover: Wear resistant synthetic rubber

Temperature: -4° F / +180° F

Application: Used for transporting the industrial waste and some material, such as dry or wet cement, slurry, coal powder, fuel by-waste material, minerals, something with sharp-angled, liquid or solid, etc.

Key Note: High wear resistant and flexibility

Part Number	Hose I.D.		Hose O.D.		Working Pressure		Burst Pressure		Min. Bend Radius		Length
	(in)	(in)	(mm)	(bar)	(psi)	(bar)	(psi)	(in)	(mm)	(ft)	
LH-CERAMIC-025	1	1.7	42	10	150	30	450	12.0	300	65	
LH-CERAMIC-032	1 1/4	2.0	50	10	150	30	450	15.0	380	65	
LH-CERAMIC-038	1 1/2	2.2	56	10	150	30	450	19.0	480	65	
LH-CERAMIC-050	2	2.8	72	10	150	30	450	24.0	600	65	
LH-CERAMIC-065	2 1/2	3.7	94	10	150	30	450	31.0	780	65	
LH-CERAMIC-075	3	4.1	105	10	150	30	450	35.0	900	65	
LH-CERAMIC-090	3 1/2	4.7	120	10	150	30	450	43.0	1,080	65	
LH-CERAMIC-100	4	5.5	140	10	150	30	450	47.0	1,200	65	
LH-CERAMIC-125	5	6.3	160	10	150	30	450	59.0	1,500	65	
LH-CERAMIC-150	6	7.5	190	10	150	30	450	71.0	1,800	65	
LH-CERAMIC-200	8	9.3	235	10	150	30	450	94.0	2,400	65	
LH-CERAMIC-250	10	11.4	290	10	150	30	450	118.0	3,000	65	
LH-CERAMIC-300	12	13.8	350	10	150	30	450	142.0	3,600	65	



Coupled Assemblies!

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.