

## Dry Bulk Material Hose



### Construction:

- Tube is abrasion resistant Natural rubber
- Cover is black NR/BR - abrasion, weather, and ozone resistant, static conductive
- Reinforcement is multiple layers of high tensile textile cord

### Operating Temperature:

- -20° F / +180° F (-29° C / +82° C)

### Safety Factor:

- 3:1

### Application:

- Dry bulk material transfer
- Ideal for dry cement, lime, and other abrasive materials

Part Number	Hose I.D.		Tube Gauge	Hose O.D.		Working Pressure	Length	Weight
	(in)	(mm)	(in)	(in)	(mm)	(psi)	(ft)	(lbs/ft)
DB-0300-4-100	3	76	1/8	3.46	88	75	100	1.14
DB-0300-6-100			3/16	3.58	91	75	100	1.46
DB-0300-8-100			1/4	3.74	94	75	100	1.80
DB-0400-4-100	4	102	1/8	4.49	114	75	100	1.49
DB-0400-6-100			3/16	4.61	117	75	100	1.91
DB-0400-8-100			1/4	4.80	122	75	100	2.62
DB-0500-4-100	5	127	1/8	5.47	139	75	100	1.97
DB-0500-6-100			3/16	5.63	143	75	100	2.50
DB-0500-8-100			1/4	5.79	147	75	100	3.34
DB-0600-4-100	6	152	1/8	6.46	164	75	100	2.34
DB-0600-6-100			3/16	6.61	168	75	100	2.95
DB-0600-8-100			1/4	6.77	172	75	100	3.95
DB-0800-4-100	8	203	1/8	8.58	218	75	100	3.64
DB-0800-6-100			3/16	8.74	222	75	100	4.45
DB-0800-8-100			1/4	8.90	226	75	100	5.77

### ***Coupled Assemblies In Stock!***

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.