

## Hot Air Blower Hose



### Construction:

- Tube is heat resistant EPDM rubber
- Cover is heat, weather, and ozone resistant EPDM rubber
- Reinforcement is multiple layers of high tensile nylon cord with dual helix wire

### Operating Temperature:

- -20° F / +350° F (-30° C / +176° C)

### Safety Factor:

- 3:1

### Application:

- Continuous hot air (at 300° F) from compressor or blower
- Dry material unloading systems

Part Number	Hose I.D.		Hose O.D.		Working Pressure (psi)	Length (ft)	Min. Bend Radius (in)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)				
HAB-BLK-0125-100	1-1/4	32	1.65	42	150	100	4	0.72
HAB-BLK-0150-100	1-1/2	38	1.92	49	150	100	5	0.84
HAB-BLK-0200-100	2	51	2.43	62	150	100	6	1.41
HAB-BLK-0250-100	2-1/2	63	3.03	77	150	100	8	1.67
HAB-BLK-0300-100	3	76	3.56	90	150	100	12	2.41
HAB-BLK-0400-100	4	102	4.74	120	150	100	16	3.72

### ***Coupled Assemblies In Stock!***

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.