

Neoprene Sheet

- CR is a synthetic polymer that offers excellent resistance to weather, ozone, sunlight, natural aging and acids
- Cloth Insertion, Nylon Insertion Available
- Cloth Impression Finish Available
- Specification And Size On the Customer's Request
- Design the product formula according to customer's special request
- Test Methods Are Corresponding with ISO Standard.
- All The colors Available



Grade	Hardness Shore A	Tensile Strength PSI	Elongation %	Temp. Range °F	Max. Width Inch	Thickness Inch
Economy CR	50±5	500	250	-13°F~+167°F	78	1/32~2
Economy CR	60±5	500	250	-13°F~+167°F	78	1/32~2
Economy CR	70±5	500	200	-13°F~+167°F	78	1/32~2
Economy CR	80±5	500	150	-13°F~+167°F	78	1/32~2
Commercial CR	40±5	725	300	-13°F~+185°F	78	1/32~2
Commercial CR	50±5	725	250	-13°F~+185°F	78	1/32~2
Commercial CR	60±5	725	250	-13°F~+185°F	78	1/32~2
Commercial CR	65±5	725	250	-13°F~+185°F	78	1/32~2
Commercial CR	70±5	725	200	-13°F~+185°F	78	1/32~2
Commercial CR	80±5	725	300	-13°F~+185°F	78	1/32~2