

Oilfield Discharge Hose - 150PSI

DO150



Inner tube: Black oil resistant NBR

Reinforcement: High tensile cord

Cover: Black, ozone, oil and aging resistant rubber compound

Temperature: -40° F / +212° F

Application: For delivery of petroleum based products up to 30% aromatic content

Part Number	Hose I.D.		Hose O.D.		Max. Length		Working Pressure		Min. Burst Pressure	
	in	mm	in	mm	ft	m	bar	psi	bar	psi
LH-DO150-025	1	25	1.4	36	200	61	10	150	30	450
LH-DO150-032	1-1/4	32	1.7	43	200	61	10	150	30	450
LH-DO150-038	1-1/2	38	1.9	49	200	61	10	150	30	450
LH-DO150-051	2	51	2.4	62	200	61	10	150	30	450
LH-DO150-063	2-1/2	63	3.0	75	200	61	10	150	30	450
LH-DO150-076	3	76	3.6	91	200	61	10	150	30	450
LH-DO150-102	4	102	4.6	117	200	61	10	150	30	450
LH-DO150-127	5	127	5.6	142	100	30.5	10	150	30	450
LH-DO150-152	6	152	6.6	167	100	30.5	10	150	30	450
LH-DO150-203	8	203	8.9	227	50	15	10	150	30	450

Coupled Assemblies In Stock!

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.