

PVC Water Suction Hose



Construction:

- Clear, flexible PVC tube
- Rigid orange PVC right-handed helix
- Reinforced with high tensile strength polyester fabric

Operating Temperature:

- -4° F / +150° F (-20° C / +66° C)
- Service temperature depends on application

Application:

- Ideal for suction and transfer
- Rental equipment, fish pond, construction, dewatering, and trash pumping
- Easy viewing of material flow
- Heavy duty water suction and discharge

Part Number	Hose I.D.		Hose O.D.		Working Pressure (psi)	Vacuum (in/HG)	Length (ft)	Min. Bend Radius (in)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
SPVC-R-0200-100	2	51	2.60	66	100	28	100	4	0.81
SPVC-R-0300-100	3	76	3.70	94	100	28	100	6	1.48
SPVC-R-0400-100	4	103	4.80	122	75	28	100	8	2.08
SPVC-R-0500-100	5	128	6.00	152	70	28	100	11	3.02
SPVC-R-0600-100	6	154	7.10	181	70	28	100	13	3.96
SPVC-R-0800-20	8	204	9.10	232	70	28	20	18	5.61
SPVC-R-1000-20	10	255	11.40	289	40	28	20	27	7.73

Coupled Assemblies In Stock!

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.