


## Tank Truck Hose



### Construction:

- Tube is nitrile synthetic rubber (NBR), RMA Class A
- Cover is black NBR, NR and CPE rubber- abrasion, oil, weather, and ozone resistant
- Reinforcement is high tensile nylon cord with dual helix wire

### Operating Temperature:

- -20° F / +180° F (-29° C / +82° C)

### Safety Factor:

- 3:1

### Application:

- Tank truck and wagon suction and delivery
- Withstands full vacuum and petroleum content up to 50%
- Ideal for a wide range of petroleum products

Part Number	Hose I.D.		Hose O.D.		Working Pressure	Length	Min. Bend Radius	Weight
	(in)	(mm)	(in)	(mm)				
TT-0100-100	1	25	1.38	35	150	100	3	0.49
TT-0125-100	1-1/4	32	1.65	42	150	100	4	0.62
TT-0150-100	1-1/2	38	1.89	48	150	100	5	0.72
TT-0200-100	2	51	2.43	62	150	100	6	0.99
TT-0250-100	2-1/2	63	2.97	75	150	100	8	1.38
TT-0300-100	3	76	3.50	89	150	100	12	1.70
TT-0350-100	3-1/2	89	4.01	102	150	100	14	2.03
TT-0400-100	4	102	4.68	119	150	100	16	3.00
TT-0450-100	4-1/2	114	5.20	132	150	100	18	3.70
TT-0500-100	5	127	5.74	146	150	100	20	4.25
TT-0600-100	6	152	6.74	171	150	100	24	5.33
TT-0800-100	8	204	8.96	228	150	100	40	8.63
TT-1000-20	10	254	11.09	282	150	20	50	13.48
TT-1200-20	12	305	13.33	339	150	20	70	20.04
TT-1400-20	14	355	15.47	393	150	20	110	26.98

### ***Coupled Assemblies In Stock!***

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.