

Water Suction and Discharge Hose



Construction:

- Tube is black Natural rubber blend compound
- Cover is black Natural rubber - abrasion, weather, and ozone resistant
- Reinforcement is multiple layers of high tensile nylon cord with helix wire

Operating Temperature:

- -20° F / +180° F (-29° C / +82° C)

Safety Factor:

- 3:1

Application:

- Delivery and suction application
- Waste water, sewage, mud, etc

| Part Number | Hose I.D. | | Hose O.D. | | Working Pressure | Length | Min. Bend Radius | Weight |
|-----------------|-----------|------|-----------|------|------------------|--------|------------------|--------|
| | (in) | (mm) | (in) | (mm) | | | | |
| WH-WSD-0075-100 | 3/4 | 19 | 1.14 | 29 | 150 | 100 | 2 | 0.39 |
| WH-WSD-0100-100 | 1 | 25 | 1.38 | 35 | 150 | 100 | 3 | 0.49 |
| WH-WSD-0125-100 | 1-1/4 | 32 | 1.65 | 42 | 150 | 100 | 4 | 0.62 |
| WH-WSD-0150-100 | 1-1/2 | 38 | 1.89 | 48 | 150 | 100 | 5 | 0.72 |
| WH-WSD-0200-100 | 2 | 51 | 2.4 | 61 | 150 | 100 | 6 | 0.92 |
| WH-WSD-0250-100 | 2-1/2 | 63 | 2.97 | 75 | 150 | 100 | 8 | 1.38 |
| WH-WSD-0300-100 | 3 | 76 | 3.48 | 88 | 150 | 100 | 12 | 1.65 |
| WH-WSD-0350-100 | 3-1/2 | 89 | 3.99 | 101 | 150 | 100 | 14 | 1.98 |
| WH-WSD-0400-100 | 4 | 102 | 4.57 | 116 | 150 | 100 | 16 | 2.53 |
| WH-WSD-0500-100 | 5 | 127 | 5.69 | 145 | 150 | 100 | 20 | 4.04 |
| WH-WSD-0600-100 | 6 | 152 | 6.68 | 170 | 150 | 100 | 24 | 4.95 |
| WH-WSD-0800-100 | 8 | 204 | 8.87 | 225 | 150 | 100 | 40 | 7.96 |
| WH-WSD-1000-20 | 10 | 254 | 10.93 | 278 | 150 | 20 | 50 | 12.11 |
| WH-WSD-1200-20 | 12 | 305 | 13.14 | 334 | 150 | 20 | 60 | 18.01 |

Coupled Assemblies In Stock!

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.