

## Water Discharge Hose - 150PSI



### DW150

**Inner tube:** Black smooth synthetic rubber

**Reinforcement:** High tensile cord

**Cover:** Black, ozone, aging and abrasion resistant rubber compound

**Temperature:** -30° F / +180° F

**Application:** For transmission of water, air, inert gases and non corrosive liquid

Part Number	Hose I.D.		Hose O.D.		Max. Length		Working Pressure		Min. Burst Pressure	
	in	mm	in	mm	ft	m	bar	psi	bar	psi
LH-DW150-032	1 1/4	32	1.7	43	200	61	10	150	30	450
LH-DW150-038	1 1/2	38	1.9	49	200	61	10	150	30	450
LH-DW150-045	1 3/4	45	2.2	56	200	61	10	150	30	450
LH-DW150-051	2	51	2.4	62	200	61	10	150	30	450
LH-DW150-063	2 1/2	63	3.0	75	200	61	10	150	30	450
LH-DW150-076	3	76	3.6	91	200	61	10	150	30	450
LH-DW150-102	4	102	4.6	117	200	61	10	150	30	450
LH-DW150-127	5	127	5.5	140	100	30.5	10	150	30	450
LH-DW150-152	6	152	6.5	166	100	30.5	10	150	30	450
LH-DW150-203	8	203	8.6	218	50	15	10	150	30	450
LH-DW150-254	10	254	10.7	272	50	15	10	150	30	450
LH-DW150-304	12	304	12.7	322	50	15	10	150	30	450

### ***Coupled Assemblies In Stock!***

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.