

Water Discharge Hose-300PSI

DW300



Inner tube: Black smooth synthetic rubber

Reinforcement: High tensile cord

Cover: Black, ozone, aging and abrasion resistant rubber compound

Temperature: -30° F / +180° F

Application: For transmission of water, air, inert gases and non corrosive liquid

Part Number	Hose I.D.		Hose O.D.		Max. Length		Working Pressure		Min. Burst Pressure	
	in	mm	in	mm	ft	m	bar	psi	bar	psi
LH-DW300-032	1 1/4	32	1.7	43	200	61	20	300	60	900
LH-DW300-038	1 1/2	38	1.9	49	200	61	20	300	60	900
LH-DW300-045	1 3/4	45	2.3	59	200	61	20	300	60	900
LH-DW300-051	2	51	2.6	65	200	61	20	300	60	900
LH-DW300-063	2 1/2	63	3.1	79	200	61	20	300	60	900
LH-DW300-076	3	76	3.6	92	200	61	20	300	60	900
LH-DW300-102	4	102	4.7	120	200	61	20	300	60	900
LH-DW300-127	5	127	5.5	140	100	30.5	20	300	60	900
LH-DW300-152	6	152	6.5	165	100	30.5	20	300	60	900
LH-DW300-203	8	203	8.5	217	50	15	20	300	60	900
LH-DW300-254	10	254	11.1	281	50	15	20	300	60	900
LH-DW300-304	12	304	13.1	333	50	15	20	300	60	900

Coupled Assemblies In Stock!

AHG can supply coupling configurations to compliment your hose requirements. We have a large selection of couplers, adaptors and hose accessories in stock and ready to ship.